

# PL SERIES

## SQUARE / RECTANGULAR BIDIRECTIONAL MULTILOUVRE DAMPER

### DESCRIPTION

- Designed for pneumatic transport of air or gases at different temperatures.
- Possibility of manufacturing Wafer type or with drilled flanges.
- Tightness between 97% and 100%.
- Possibility of using an air sealing system to increase tightness up to 100%
- Various constructions materials and seal and stuffing materials available.
- Face-to-face distance in accordance with **CMO Valves** standards. Other distances upon request.
- Other distances and configurations upon request.

### GENERAL APPLICATIONS

Butterfly damper valves are suitable to work with a wide range of air and gases. They are particularly suitable for controlling the flow of gas in pipelines.

Used mainly in:

- Co generation plants.
- Thermal power stations.
- Electrical power stations.
- Chemical plants.
- Energy sector.
- ...

### SIZES

From 125 x 125 to 3000 x 3000.

*Other DN's on request.*

### WORKING PRESSURE ( $\Delta P$ )

The standard maximum working pressure is <0.5 bar and temperature is 600°C.

*Other pressures and temperatures on request.*

### TIGHTNESS

The standard tightness for these valves from **CMO Valves**, ranges between 97% and 100%. To obtain 100% tightness at high temperatures double clapper systems must be applied and sealed by air injection.

### FLANGES

Flange and inter face connections are according to the standard of **CMO Valves**, but can also be manufactured to the requirements of the customer on request.

### DIRECTIVES

See document of directives applicable to **CMO Valves**.



*For further information on categories and zones please contact **CMO Valves**. Technical-Commercial Department.*

### QUALITY DOSSIER

- The tightness of the seat area is measured with gauges.
- Material and testing certificates can be supplied on request.



PL SERIES